

## TABLE 5-B

### MINIMUM REQUIREMENTS FOR STRUCTURAL COMPOSITION OF PAVEMENTS

<b><u>Street Classification</u></b>	<b><u>Flexible Pavements</u></b>	<b><u>Rigid Pavements<sup>1</sup></u></b>
MARGINAL LAND ACCESS Residential	8" Cr. St. 1 1/2" Bituminous Concrete Bind. 1 1/2" Bituminous Concrete Surf.	6" P.C.C.
LOCAL Residential	8" Cr. St. 2" Bituminous Concrete Bind. 1 1/2" Bituminous Concrete Surf.	6" P.C.C.
COLLECTOR Residential	8" Cr. St. 3" Bituminous Concrete Base Course 1 1/2" Bituminous Concrete Surf.	7" P.C.C. with Fabric 4" Cr. St.
LOCAL Commercial and Industrial	8" Cr. St. 3" Bituminous Concrete Base Course 2" Bituminous Concrete Surf.	7" P.C.C. with Fabric 4" Cr. St.
COLLECTOR Commercial and Industrial	8" Cr. St. 4" Bituminous Concrete Base Course 1 1/2" Bituminous Concrete Bind. 1 1/2" Bituminous Concrete Surf.	8" P.C.C. with Fabric 4" Cr. St.

<sup>1</sup> Joints in rigid pavement shall be in accordance with IDOT BLR 10-4.

**ABBREVIATIONS:**

Cr. St.	=	Crushed Stone
P.C.C.	=	Unreinforced Portland Cement Concrete